GSWX-26

SM Cylindrical Watch Crystal

- Low cost
- Formed leads for SM
- Industrial temperature range
- Miniature size for high density applications




CONFIGURABLE OPTIONS	
Parameter	Option Code
Calibration tolerance	
±20ppm	
±15ppm	А
±10ppm	D
Circuit condition	
Any	
12.5pF	
8pF	
6pF	

SPECIFICATIONS

32.768kHz
32.768KHZ
ø2.0 x 6.1mm
-40 to +85°C
-55 to +125°C
+25°C ±5°C
-0.034 ± 0.006 ppm/°C ² typ
1.35pF typ
3fF typ
35kΩ max @ 25°C
±1ppm typ, ±3ppm max
1.0µW max
240°C, 10 sec max

PACKAGE DRAWING



ORDERING INFORMATION

To request a quotation for the GSWX-26 please use the configurable options form to choose the options you require and then submit your configured product to our team. Our expert advisers are always happy to help with your requirements and can be contacted on +44 1460 256 100 or at sales@golledge.com.

Following product selection you will be issued with a seven character Golledge part number. Your Golledge part number is the internationally accepted Golledge manufacturing part number (MPN) that should be used for all project documentation, including bills of materials (BoMs) and purchase orders.

If you have any queries regarding any of our documentation our dedicated sales team will be happy to help.

HANDLING & STORAGE



🙏 Human Body Model (HBM) 1A (250V to <500V)



Moisture Sensitivity Level (MSL): 1 (or not applicable)

CONSTRUCTION

Press seal cylinder

COMPLIANCE



Lead-free (< 0.1% by weight)



RoHS compliant with no exemptions.

<u>See our</u>

declaration



REACH compliant. See our statement



Free of conflict minerals. <u>See our declaration</u>



Free of Halogens. <u>See our declaration</u>



Free of Ozone-depleting substances. <u>See our</u>

declaration