

# HCD666

## Fast Warm Up OCXO with CMOS

### Output and European Pin-out



- Fast warm up
- Temperature stability down to 1ppb
- Single 12V supply (12V ~ 30V optional)
- Standard European pin-out
- Custom options available

### CONFIGURABLE OPTIONS

| Parameter                               | Option Code |
|---|-------------|
| <b>Frequency</b>                        |             |
| <b>Ageing per day (at despatch)</b>     |             |
| Any                                     |             |
| < 1x10 <sup>-9</sup>                    | D           |
| < 5x10 <sup>-10</sup>                   | E           |
| < 2x10 <sup>-10</sup>                   | F           |
| <b>Temperature stability</b>            |             |
| Any                                     |             |
| < 1x10 <sup>-8</sup>                    | R           |
| < 5x10 <sup>-9</sup>                    | S           |
| < 3x10 <sup>-9</sup>                    | T           |
| < 1x10 <sup>-9</sup>                    | V           |
| <b>Operating temperature range</b>      |             |
| Any                                     |             |
| 0 to +50 °C                             | A           |
| -10 to +60 °C                           | C           |
| -20 to +70 °C                           | F           |
| -40 to +70 °C                           | G           |
| <b>Supply voltage (V<sub>DD</sub>)</b>  |             |
| +12V (±0.5V)                            | N           |
| Other options from 12~30V               |             |
| <b>Close-in phase noise (@ 5.0MHz)</b>  |             |
| Any                                     |             |
| < -110 dBc/Hz @ 1Hz, <-135 @ 10Hz       |             |
| < -123 dBc/Hz @ 1Hz, <-140 @ 10Hz       | Z           |
| < -150 dBc/Hz @ 100Hz                   |             |
| <b>Close-in phase noise (@ 10.0MHz)</b> |             |
| Any                                     |             |
| < -95 dBc/Hz @ 1Hz, <-130 @ 10Hz        |             |
| < -108 dBc/Hz @ 1Hz, <-135 @ 10Hz       | Z           |
| < -145 dBc/Hz @ 100Hz                   |             |



## ORDERING INFORMATION

---

To request a quotation for the HCD666 please use the configurable options form to choose the options you require and then submit your configured product to our team. Our expert advisers are always happy to help with your requirements and can be contacted on +44 1460 256 100 or at [sales@golledge.com](mailto:sales@golledge.com).

Following product selection you will be issued with a seven character Golledge part number. Your Golledge part number is the internationally accepted Golledge manufacturing part number (MPN) that should be used for all project documentation, including bills of materials (BoMs) and purchase orders.

If you have any queries regarding any of our documentation our dedicated sales team will be happy to help.

## CONSTRUCTION

---

Solder sealed metal can

## HANDLING & STORAGE

---



Human Body Model (HBM) 1A (250V to <500V)



Moisture Sensitivity Level (MSL): 1 (or not applicable)

## COMPLIANCE

---



Lead-free (< 0.1% by weight )



RoHS compliant with no exemptions. [See our declaration](#)



REACH compliant. [See our statement](#)



Free of conflict minerals. [See our declaration](#)



Free of Halogens. [See our declaration](#)



Free of Ozone-depleting substances. [See our declaration](#)